


Pipeline Safety Division Trivia (Session 3)



QUESTION 1



Next



Previous



Bell



Horn



Cheer



Silence

Each pipeline that is under cathodic protection must be tested at least _____?

INCORRECT

Twice each calendar year, but with intervals not exceeding 7.5 months.

**CORRECT
192.465(a)**

Once each calendar year, but with intervals not exceeding 15 months.

INCORRECT

Six times a year, but with intervals not exceeding 2.5 months

INCORRECT

None of the above



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 2



Next



Previous



Bell



Horn



Cheer



Silence

For hazardous liquid pipelines air or inert gas may be used as the test medium in low-stress pipelines

True (195.306 (d))

False



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 3



Next



Previous



Bell



Horn



Cheer



Silence

49 CFR part 195 defines a pipeline facility as new and existing pipe, rights-of-way and any equipment, facility, or building used in the transportation of hazardous liquids or carbon dioxide.

True (195.2)

False



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 4



Next



Previous



Bell



Horn



Cheer



Silence

For hazardous liquids what construction records are required?

INCORRECT

The amount, location, and cover of each size of pipe installed.

INCORRECT

The location of each valve and corrosion test station.

CORRECT
195.266

All of the Above

INCORRECT

The location of each overhead crossing.



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 5



Next



Previous



Bell



Horn



Cheer



Silence

A _____ location is any class location unit that has more than 10 but less than 46 buildings meant or human occupancy.

INCORRECT

Class 1

**CORRECT
(192.5)**

Class 2

INCORRECT

Class 3

INCORRECT

Class 4



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 6



Next



Previous



Bell



Horn



Cheer



Silence

In reference to plastic pipe, tracer wire may be wrapped around the pipe.

True

False (192.321 (e))



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 7



Next



Previous



Bell



Horn



Cheer



Silence

Service regulator vents and relief vents must terminate outdoors, and the outdoor terminal must

INCORRECT

Be rain and insect resistant.

INCORRECT

Be located at a place where gas from the vent can escape freely into the atmosphere and away from any opening into the building.

INCORRECT

Be protected from damage caused by submergence in areas where flooding may occur.

CORRECT
192.355(b)

All of the above



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 8



Next



Previous



Bell



Horn



Cheer



Silence

Each regulator station controlling the flow or pressure of gas in a distribution system must have a valve installed on the inlet piping at a distance from the regulator station sufficient to _____.

CORRECT
192.181 (b)

Permit the operation of the valve during an emergency that might preclude access to the station.

INCORRECT

Ensure that the regulator is properly venting.

INCORRECT

Ensure the neighboring households will not have a valve in their yard.

INCORRECT

None of the above



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 9



Next



Previous



Bell



Horn



Cheer



Silence

A combustible gas in a distribution line must contain a natural odorant or be odorized so that at a concentration in air of one-fifth of the lower explosive limit, the gas is readily detectable by a person with a normal sense of smell.

True (192.625 (a))

False



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 10



Next



Previous



Bell



Horn



Cheer



Silence

Which type of in-line inspection tool is commonly run after construction to detect dents?

INCORRECT

Ultrasonic (UT)

INCORRECT

Magnetic Flux Leakage

CORRECT

Geometry

INCORRECT

None of the above



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 11



Next



Previous



Bell



Horn



Cheer



Silence

Each valve, the use of which may be necessary for the safe operation of a distribution system, must be checked and serviced at intervals _____.

INCORRECT

None of the Above

INCORRECT

not exceeding 2.5 months, but at least six times each calendar year.

INCORRECT

not exceeding 7.5 months, but at least twice each calendar year.

CORRECT
192.747(a)

not exceeding 15 months, but at least once each calendar year.



Next



Previous



Bell



Horn



Cheer



Silence

QUESTION 12



Next



Previous



Bell



Horn



Cheer



Silence

192.614 Damage Prevention applies to all Type C gathering lines.

True

False



Next



Previous



Bell



Horn



Cheer



Silence